



Make It Yours.

Hyper 212 LED Turbo White Edition



Hyper 212 LED Turbo White Edition is equipped with a white top cover and dual PWM Fan with White LEDs and provides the best airflow and static pressure to take the heat away. And four direct contact heat pipes with funnel shaped aluminum fins provide the optimized CPU coolers for great performance. Moreover, the improved universal bracket designs ensure easy and worry free installation on all platforms.

Features

Sleek Finishing – Pearl white paint to the top cover for a more refined look

Precise Air Flow - Precise stacked fin array decreases airflow resistance which allows for cooler air flow into the heatsink

Direct Contact Technology - 4 heatpipes with Exclusive Direct Contact Technology providing effective and excellent heat dissipation

Dual XtraFlo PWM Fans – Come with white LEDs and wide speed range can be fine-tuned for maximum cooling performance or silent operation

Snap and Play - Intuitive fan bracket design makes upgrading and removing the fan a breeze.

EAN code	4719512084618
UPC code	884102057113
Net weight (Kg)	0.831
Gross weight (Kg)	1.075
Carton dimension (L x W x H)	53.5 x 33 x 25.3 cm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	3840	48	N/A
40'	7680	48	N/A
40 HQ	8640	54	N/A

Specifications & Packing Information

Product Name		Hyper 212 LED Turbo White Edition
Product Number		RR-212TW-16PW-R1
CPU socket*		Intel® LGA 2066/2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 AMD AM4/ AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1
Dimensions (L x W x H)		120 x 108 x 160 mm (4.7 x 4.3 x 6.3 inch)
Heat Sink Material		4 Heat Pipes / Aluminum Fins/ Direct Contact
Fan	Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)
	Quantity	2 PCS
	Speed	600 ~ 1600 RPM (PWM) ± 10%
	Air Flow	66.3 CFM (Max)
	Air Pressure	1.7 mmH ₂ O
	MTTF	40,000 Hours
	Noise Level	9 ~ 31 dBA
	Power Connector	4-Pin (PWM)
	Rated Voltage	12 VDC
	Rated Current	0.19 A
Safety Current	0.32 A	
Power Consumption	2.28 W	
Warranty		2 Years
*For the latest CPU support information, please visit our website		

Key Features



SLEEK FINISHING

Pearl white paint to the top cover for a more refined look



PRECISE AIR FLOW

Precise stacked fin array decreases airflow resistance which allows for cooler air flow into the heatsink



DIRECT CONTACT TECHNOLOGY

4 heat pipes with exclusive Direct Contact Technology providing effective and excellent heat dissipation



DUAL XTRAFLO PWM FANS

Come with white LEDs and wide speed range can be fine-tuned for maximum cooling performance or silent operation



UNIVERSAL MOUNTING KITS DESIGN

The improved universal bracket design ensures easy and worry free installation on all platforms