

Dual-Monitor USB 3.0 Docking Station with HDMI & DVI/VGA

Product ID: USB3SDOCKHDV



This USB 3.0 dock combines three USB 3.0 ports, headphone and microphone audio connectors, and a Gigabit Ethernet RJ45 port, into a single docking station for maximum productivity.

Offering flexible dual video combinations right out-of-the-box, this universal laptop docking station features HDMI, DVI and VGA external monitor outputs. Each video output supports HD video resolutions (2048x1152 max) and HD video playback for an ideal solution to expanding your notebook's video capability.

Available display combinations:

- HDMI + VGA
- HDMI + DVI

The built-in USB hub features three USB 3.0 ports for connecting extra peripherals such as external hard drives or a wired mouse, as if they are connected directly to your laptop.

The integrated RJ45 Ethernet port supports speeds of 10/100/1000 Mbps, giving you an instant connection to a wired network.

StarTech.com laptop docking stations can be used for cost savings and faster deployment with just a single cable. This USB 3.0 Docking Station is backed by a competitive 3-year warranty and free lifetime Technical Support.

Certifications, Reports and Compatibility

Applications

Shared workspaces



- Hot/Remote desks
- Convert laptop to desktop workstation

Features

- Connect dual monitors using either HDMI + DVI-D, or HDMI + VGA combinations
- Connect devices with 3 USB 3.0 ports
- Connect to wired networks with the built-in 10/100/1000 Mbps compatible RJ45 Ethernet port
- TAA compliant GSA schedule purchases

Hard	lware
------	-------

Warranty 3 Years

4K Support No

Fast-Charge Port(s) No

Displays Supported 2

Bus Type USB 3.0

Industry Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, USB 3.0

Chipset ID DisplayLink - DL-3900

Genesys Logic - GL3520

Realtek - RTL8211F

Performance

Maximum Data Transfer

5 Gbps (USB 3.0)

2 Gbps (Ethernet; Full-Duplex)

Maximum Analog Resolutions

Rate

2048x1152 (VGA)

Maximum Digital Resolutions

1920x1200 (DVI-D)

1920x1080 (HDMI)

Lower resolutions are also supported.

Audio Specifications The HDMI port supports audio output



Type and Rate USB 3.0 - 5 Gbit/s

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Full Duplex Support Yes

Connector(s)

Connector Type(s) 3.5 mm Mini-Jack (3 Position)

DVI-D (25 pin)

HDMI (19 pin)

RJ-45

USB Type-A (9 pin) USB 3.0 (5 Gbps)

USB Type-B (9 pin) USB 3.0

VGA (15 pin, High Density D-Sub)

Software

OS Compatibility Windows XP SP3 (32-bit), Vista, 7, 8, 8.1, 10, 11

macOS 10.6 - 10.12, 10.14 - 10.15, 11.0, 12.0, Chrome v69+

Special Notes / Requirements

System and Cable Requirements

USB 3.0 enabled computer system with available USB 3.0 port

HDMI (and either DVI-D or VGA if dual display is desired) enabled display device(s) e.g. monitor, projector, HTDV, etc. with

cables

Available AC electrical outlet

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 0.9 A

Output Voltage 5 DC

Output Current 4 A



Center Tip Polarity Positive

Plug Type B

Power Consumption (In

Watts)

Environmental

Operating Temperature 0C to 40C (32F to 104F)

20

Storage Temperature -10C to 60C (14F to 140F)

Humidity 0~90% RH

Physical Characteristics

Color Black

Material Plastic

Cable Length 35.4 in [90 cm]

Product Length 12.0 in [30.4 cm]

Product Width 7.0 in [17.8 cm]

Product Height 1.7 in [44 mm]

Weight of Product 10.4 oz [295 g]

Packaging Information

Package Length 11.7 in [29.6 cm]

Package Width 7.7 in [19.5 cm]

Package Height 2.6 in [66 mm]

Shipping (Package)

Weight

31.0 oz [878 g]

What's in the Box

Included in Package Docking Station

0.9m USB 3.0 Cable

Universal Power Adapter (NA/EU/UK/AU)

Installation CD



Instruction Manual

*Product appearance and specifications are subject to change without notice.